


LAMP UNITS





FIRECO

LAMP UNITS

Index.

01

LED FLOODLIGHTS

- *floodlights LZ*
- *floodlights DUO LED*



Bosch Car Service

High Precision Motor Products

BERGHS DOTTUN CAMP AN CHURRAIGH

WESTWARD BOSCH
ESTABLISHED 1906
100% GENUINE
100% GENUINE

LAMP UNITS

The traditional application field of telescopic masts is lighting. In fact, various types and different combinations of floodlights can be mounted on the mast head and thanks to the use of the tilt & turn unit the operator can direct the lighting beam to different positions and illuminate large areas.

Fireco offers a range of LED floodlights with high energy efficiency that permits to illuminate large areas, that have many advantages thanks to their technology: high efficiency, long life, shock and wear resistance, low voltage power supply, reduced consumption and low operating temperatures



LED FLOODLIGHTS

FEATURES

- ENERGY SAVING: LED GENERATES A LUMINOUS FLUX APPROXIMATELY 5 TIMES HIGHER THAN INCANDESCENT AND HALOGEN LAMPS
- MINIMUM HEAT DEVELOPMENT
- LOW POWER OPERATION
- IMMEDIATE COLD START
- LONGER LIFE: LED LAMPS LAST ON AVERAGE 50,000 HOURS, APPROXIMATELY 15 YEARS
- LOWER MAINTENANCE COSTS
- GREATER STRENGTH AND RESISTANCE TO HUMIDITY E VIBRATIONS
- POSSIBILITY OF RECYCLING 99% OF THE COMPONENTS WITH BENEFITS FOR THE ENVIRONMENT

FLOODLIGHTS LZ

The floodlights designed and developed by Fireco allow telescopic masts to be completed with high-quality lighting to provide firefighters or rescue workers with the best available support. They can be mounted on a Tilt & Turn unit directly or on the mast head, if required, also in a 360° top side position (i.e. 3 floodlights mounted at 120° or 4 floodlights at 90°).

The latest series of floodlights with LED technology developed by Fireco are the **LZ** LEDs which offer an excellent mix of energy-efficient performance and great light output. They are available in 50W, 80W, 100W, 200W, 300W or 400W versions and with 60° or 90° light beams.



LZ 50 W

LZ 80 W

LZ 50 W	NEW FEATURES	
	Consumption	50 W
	Power supply	12 to 40 Vdc
	Power absorption	4,16 A- 1,25 A
	Color temperature	5000 K
	Light flux	8800 LM
	IP degree	IP 66
	Weight	1,1 kg
	Dimensions	128x148x70 mm
	Operating temperature	-40°C to + 85°C

LZ 80 W	NEW FEATURES	
	Consumption	80 W
	Power supply	12 to 40 Vdc
	Power absorption	6,66 A - 2,00 A
	Color temperature	5000 K
	Light flux	11500 LM
	IP degree	IP 66
	Weight	1,1 kg
	Dimensions	128x148x70 mm
	Operating temperature	-40°C to + 85°C

LZ 100 W

FEATURES	
Consumption	100 w
Power supply	12 to 24 Vdc - 130 to 230 Vac
Power absorption	8,3/4,13 A - 1,5/0,75 A
Color temperature	5000 K
Light flux	17600 LM
IP degree	IP 66
Weight	3 kg
Dimensions	348x161x96 mm
Operating temperature	-40°C to + 85°C

LZ 100 W



LZ 200 W

FEATURES	
Consumption	200 W
Power supply	12 to 24 Vdc - 130 to 230 Vac
Power absorption	16,7/8,3 A - 1,5/7,5 A
Color temperature	5000 K
Light flux	35200 LM
IP degree	IP 66
Weight	5,8 kg
Dimensions	362x224x142 mm
Operating temperature	-40°C to + 85°C

LZ 200 W





LZ 300 W



LZ 300 W

FEATURES	
Consumption	300 W
Power supply	12 to 24 Vdc - 130 to 230 Vac
Power absorption	25/12,5 A - 1,5/0,75 A
Color temperature	5000 K
Light flux	52800 LM
IP degree	IP 66
Weight	7,6 kg
Dimensions	517x224x142 mm
Operating temperature	-40°C to + 85°C

LZ 400 W



LZ 400 W

FEATURES	
Consumption	400 W
Power supply	12 to 24 Vdc - 130 to 230 Vac
Power absorption	33/16,6 A - 1,5/0,75 A
Color temperature	5000 K
Light flux	70400 LM
IP degree	IP 66
Weight	10,8 kg
Dimensions	674x224x142 mm
Operating temperature	-40°C to + 85°C

FLOODLIGHTS DUO LZ

Natural evolution of the LZ, the **Duo LZ** floodlights are Fireco's most complete LED lighting solution. It allows operators to adapt the lighting to the environmental conditions of the operating site by switching between two different color temperatures: a classic white daylight (5700 K) or a warmer selective yellow light (2700 K).

Especially suitable for foggy or snowy environments, the yellow light will help to avoid the effects of glare. Whatever the weather, the Duo LZ is ready to guarantee the best visibility in every situation.



DUO LZ 100 W

DUO LZ 100 W	FEATURES	
	Consumption	100 W
	Power supply	12 to 40 Vdc
	Power absorption	8,3/4.15 A- 1.5/0.75 A
	Color temperature	2700 K / 5700 K
	Light flux	8000 LM/ 8900 LM
	IP degree	IP 66
	Weight	3 kg
	Dimensions	348x161x96 mm
	Operating temperature	-40°C to + 85°C

DUO LZ 200 W

DUO LZ 200 W	FEATURES	
	Consumption	200 W
	Power supply	12 to 40 Vdc
	Power absorption	16,7/8,3 A
	Color temperature	2700 K / 5700 K
	Light flux	18700 LM / 20370 LM
	IP degree	IP 66
	Weight	6,5 kg
	Dimensions	362X224X142 mm
	Operating temperature	-40°C to + 85°C



GALLERY Lamp Units





Credits

Copyright 2023- FIRECO - All rights reserved

ITALIAN HEADQUARTERS

Fireco S.r.l.

Via E.Fermi, 56
25064 GUSSAGO (BS) - ITALY
Tel.:+39 030 3733916
Fax:+39 030 3733762
info@fireco.eu
www.fireco.eu

FIRECO.EU



BELGIUM

Fireco Systems N.V.

Diestersteenweg, 142
3510 KERMT (HASSELT) - BELGIUM
Tel.:+32 11851602
Fax:+32 11851604
info@fireco.be
www.fireco.be

FRANCE

Euromast S.a.r.l.

101 Rue Louis Armand
73420 MERY - FRANCE
Tel.:+33 479349215
Fax:+33 479349216
fireco@euromast.fr
www.euromast.fr

SPAIN

Hispamast S.L.

C/Estaño, 30
28510 CAMPO REAL (MADRID) - SPAIN
Tel.:+34 918733733
Fax:+34 918765141
info@hispamast.com
www.hispamast.com

USA

Fireco US

1740 N Gateway Blvd
FRESNO, CA 93727 - USA
Tel.: +1 559 353-2823
Fax.: +1 559 255-7012
info@firecousa.com
www.firecousa.com

MALAYSIA

Fireco Asia Sdn Bhd

9, Jalan TP 3/2, Taman Perindustrian UEP
47620 SUBANG JAYA - MALAYSIA
Tel.:+603 8011 2300
Fax:+603 8081 2367
gc@fireco-asia.com
www.fireco-asia.com

AUSTRALIA

EVTA Group PTY LTD

12 Meek Street,
NEW GISBORNE, VICTORIA, 3438 - AUSTRALIA
Tel.:+61 354207444
Fax:+61 354207834
info@evtagroup.com.au
www.evtagroup.com.au

MOROCCO

Euro -Fireco

Résidence les jardins Al Noamane
Rue Izdihar, Bouskoura,
Casablanca - MOROCCO
Tel.:+212 5220-66343
info@euro-fireco.com
www.euro-fireco.com